

PGDQ2.MH14014
Marking and Labeling Systems - Component

| No. | Application Surface | Max Temp (°C) | Min Temp (°C) | Indoor Use | Outdoor Use | Additional Conditions |
|--------------|---|---------------------|------------------|---------------|----------------|--------------------------|
| MIRVY | | | | | | |
| | Acrylic paint (AC PT) | 80 | -29 | X | - | O |
| | Alkyd paint (AK PT) | 80 | -29 | X | - | O |
| | Aluminum (AL) | 80 | -29 | X | - | O |
| | Epoxy painted metal | 80 | - | X | - | O |
| | Galvanized steel (GS) | 80 | -40 | X | - | O |
| | Porcelain (PRCLN) | 80 | -40 | X | - | O |
| | Stainless steel (SS) | 80 | -29 | X | - | O |
| | Unsaturated polyester - thermoset (UP) | 80 | -29 | X | - | O |
| | Acrylonitrile butadiene styrene (ABS) | 60 | -29 | X | - | O |
| | Polyphenylene oxide/ether (PPOX) | 60 | - | X | - | - |
| | Polystyrene (PS) | 60 | - | X | - | - |
| | Polypropylene (PP) | 40 | -29 | X | - | - |

PGDQ8.MH14014
**Marking and Labeling Systems Certified for Canada -
Component**

| Model No. | Application Surface | Max Temp (°C) | Indoor Use | Outdoor Use | Additional Conditions |
|-----------------------|------------------------|---------------------|---------------|----------------|--------------------------|
| MIRVY (Type A) | | | | | |
| | Metals | 100 | X | - | - |
| | Plastic Group I | 100 | X | - | - |
| | Plastic Group II | 80 | X | - | - |
| | Plastic Group III | 80 | X | - | - |
| | Plastic Group V | 80 | X | - | - |
| | Plastic Group VI | 80 | X | - | - |
| | Plastic Group VII | 80 | X | - | - |
| | Plastic Group VIII | 80 | X | - | - |