

## PGDQ2.MH14014

### Marking and Labeling Systems - Component

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRVY IV</b>						
	Acrylic paint (AC PT)	100	-40	X	X	-
	Alkyd paint (AK PT)	100	-40	X	X	-
	Nylon - polyamide (PA)	100	-40	X	X	-
	Stainless steel (SS)	100	-40	X	X	-
	Aluminum (AL)	80	-40	X	X	-
	Epoxy powder paint (EP PDR PT)	80	-40	X	-	-
	Southern yellow pine	80	-	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-	X	-	-
	Galvanized steel (GS)	60	-40	X	X	-
	Polyester paint (PER PT)	60	-40	X	X	-
	Acrylonitrile EPDM styrene (AES) plastic	40	-40	X	X	-
	Acrylonitrile butadiene styrene (ABS)	40	-40	X	X	-
	Polyethylene (PE)	40	-40	X	X	-
	Polyphenylene oxide/ether (PPOX)	40	-40	X	X	-
	Polypropylene (PP)	40	-40	X	X	-
	Polystyrene (PS)	40	-40	X	X	-

## PGDQ8.MH14014

### Marking and Labeling Systems Certified for Canada - Component

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRVY IV (Type A)</b>					
	Metals	100	X	X	-
	Plastic Group I	100	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VIII	80	X	X	-
	Acrylonitrile EPDM styrene (AES) plastic	40	X	X	-