

PGJI2.MH25872

Printing Materials - Component

Dsg.	Application Surface	Max Temp (C)	Min Temp (C)	Indoor Use	Outdoor Use	Additional Conditions
Printed label dsg: Therman V Inks: 1, 2						
	Acrylic paint (AC PT)	80	-40	X	-	O
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	O
	Alkyd paint (AK PT)	80	-40	X	-	O
	Aluminum (AL)	80	-40	X	-	O, PL
	Galvanized steel (GS)	80	-40	X	-	O
	Phenolic - Phenol Formaldehyde (PH)	80	-40	X	-	O
	Polyester paint (PER PT)	80	-40	X	-	O
	Polyethylene (PE)	80	-40	X	-	O
	Polyphenylene oxide/ether (PPOX)	80	-40	X	-	O
	Polypropylene (PP)	80	-40	X	-	O
	Polystyrene (PS)	80	-40	X	-	O
	Southern yellow pine	80	-40	X	-	PL
	Stainless steel (SS)	80	-40	X	-	O
	Textured aluminum	80	-40	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-40	X	-	PL
	Epoxy paint (EP PT)	60	-	X	-	-