

PGJI2.MH25872

Printing Materials - Component

Dsg.	Application Surface	Max Temp (C)	Min Temp (C)	Indoor Use	Outdoor Use	Additional Conditions
Printed label dsg: Therman VI						
Inks: 2, 3						
	Acrylic paint (AC PT)	150	-40	X	-	O
	Alkyd paint (AK PT)	150	-40	X	-	O
	Aluminum (AL)	150	-40	X	-	O
	Epoxy paint (EP PT)	150	-40	X	-	-
	Epoxy/urethane powder paint	150	-40	X	-	-
	Galvanized steel (GS)	150	-40	X	-	-
	Polyester paint (PER PT)	150	-40	X	-	O
	Polyester powder paint (PER PDR PT)	150	-40	X	-	-
	Porcelain (PRCLN)	150	-40	X	-	-
	Stainless steel (SS)	150	-40	X	-	-
	Textured alkyd enamel powder coat paint	150	-40	X	-	-
	Textured alkyd enamel/melamine paint	150	-40	X	-	-
	Melamine (ME)	100	-40	X	-	-
	Nylon - polyamide (PA)	100	-40	X	-	O
	Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
	Unsaturated polyester - thermoset (UP)	100	-40	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	O
	Polycarbonate (PC)	80	-40	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-40	X	-	O
	Textured polypropylene	80	-40	X	-	-

PGJI8.MH25872

Printing Materials Certified for Canada - Component

Model Dsg.	Application Surface	Max Temp (C)	Indoor Use	Outdoor Use	Additional Conditions
Printed label dsg: Therman VI (Type A)					
Inks: 1, 2					
	Metals	150	X	-	-

	Textured alkyd enamel/melamine paint	150	X	-	-
	Textured alkyd powder coat paint	150	X	-	-
	Plastic Group II	80	X	-	-
	Plastic Group III	80	X	-	-
	Plastic Group IV	80	X	-	-
	Plastic Group V	80	X	-	-
	Plastic Group VI	80	X	-	-
	Plastic Group VII	80	X	-	-
	Plastic Group VIII	80	X	-	-
	Textured polypropylene	80	X	-	-